

Prepark Comfort

Technical data

Type of wood	Oak
Grading	15
Colour	
Surface structure	
Surface treatment	lacquered
Format	480 x 117 x 10 mm
Number of layers	1
Top layer thickness	~ 3.5 mm
Laying method	glued to subfloor
Packing unit	3.01 m ² /package
Wood origin	Oak: Europe
Label health and sustainability	
Wood label	Wood from controlled sources
eco-bau	«eco-1», very suitable for Minergie-ECO, 1st priority ECO-BKP/Eco-Devis
Sentinel Haus institute	fulfilled
Cradle to Cradle Certified TM	
Label on VOC-emissions for France	A+
Release of formaldehyde according to EN 717-1	E 1
Density - top layer	~ 650 kg/m ³
Grammage	~ 5.33 kg/m ²
Hardness Brinell - top layer *1	~ 38 N/mm ²
Shrinkage and swelling *2	0.25 %
Floor heating (Thermal resistance)	very convenient (~0.1 m ² K/W)
Moisture content	5-9 %
Fire Resistance acc. to EN 14342 and EN 13501-1	Dfl-s1
Slip resistance grade	
according to CEN/TS 15676 *3	USRV 43
Product standard	EN 13488

*1 at moisture content of 7 %

*2 top layer at free storage, based on a humidity change of 1 %

*3 Pendulum test

Date: 11.05.21