

# Unopark

## Technical data

|                                                 |                                                                 |
|-------------------------------------------------|-----------------------------------------------------------------|
| Type of wood                                    | Oak                                                             |
| Grading                                         | 14                                                              |
| Colour                                          | Crema                                                           |
| Surface structure                               | unbrushed                                                       |
| Surface treatment                               | B-Protect®                                                      |
| Format                                          | 470 x 70 x 11 mm                                                |
| Number of layers                                | 2                                                               |
| Top layer thickness                             | ~ 4 mm                                                          |
| Laying method                                   | glued to subfloor                                               |
| Connection                                      | Tongue + groove                                                 |
| Packing unit                                    | 2.64 m <sup>2</sup> /package                                    |
| Wood origin                                     | Oak: Europe, Spruce: Europe                                     |
| Label health and sustainability                 |                                                                 |
| Wood label                                      | Wood from controlled sources                                    |
| eco-bau                                         | «base», does not infringe criteria of exclusion of Minergie-ECO |
| Sentinel Haus institute                         | fulfilled                                                       |
| Cradle to Cradle Certified®                     |                                                                 |
| Label on VOC-emissions for France               | A+                                                              |
| Release of formaldehyde according to EN 717-1   | E 1                                                             |
| Density - top layer                             | ~ 650 kg/m <sup>3</sup>                                         |
| Grammage                                        | ~ 4.95 kg/m <sup>2</sup>                                        |
| Hardness Brinell - top layer *1                 | ~ 38 N/mm <sup>2</sup>                                          |
| Shrinkage and swelling *2                       | 0.25 %                                                          |
| Floor heating (Thermal resistance)              | 100% convenient ( ~0.082 m <sup>2</sup> K/W )                   |
| Moisture content                                | 5-9 %                                                           |
| Fire Resistance acc. to EN 14342 and EN 13501-1 | Dfl-s1                                                          |
| Slip resistance grade                           |                                                                 |
| according to CEN/TS 15676 *3                    | USRV 99                                                         |
| according to DIN-EN 51130 *4                    | R10                                                             |
| according to ÖNORM Z 1261 *5                    | Class 1                                                         |
| Product standard                                | EN 13489                                                        |

\*1 at moisture content of 7 %

Date: 27.04.24

\*2 top layer at free storage, based on a humidity change of 1 %

\*3 Pendulum test

\*4 inclined plane

\*5 Coefficient of friction