

Villapark

Technical data

| | |
|---|---|
| Type of wood | Oak |
| Grading | 46 |
| Colour | Mandorla |
| Surface structure | beveled 2V, deep brushed |
| Surface treatment | matt lacquered |
| Format | 2100 x 190 x 9.5 mm |
| Number of layers | 2 |
| Top layer thickness | ≥ 2.5 mm |
| Laying method | glued to subfloor |
| Connection | Tongue + groove |
| Packing unit | 2.4 m ² /package |
| Wood origin | Oak: Europe, HDF: Germany |
| Label health and sustainability | |
| Wood label | Wood from controlled sources |
| eco-bau | |
| Sentinel Haus institute | |
| Cradle to Cradle Certified® | |
| Label on VOC-emissions for France | |
| Release of formaldehyde according to EN 717-1 | |
| Density - top layer | ~ kg/m ³ |
| Grammage | ~ 8 kg/m ² |
| Floor heating (Thermal resistance) | 100% convenient (~0.064 m ² K/W) |
| Moisture content | % |
| Fire Resistance acc. to EN 14342 and EN 13501-1 | Cfl-s1 |
| Slip resistance grade | |
| according to CEN/TS 15676 *1 | USRV 57 |
| Product standard | EN 13489 |

*1 Pendulum test

Date: 27.04.24